Atty Docket No.: 10005732-1

App. Ser. No.: 09/882, 038

# IN THE CLAIMS:

Please find a listing of the claims below. The statuses of the claims are shown in parentheses.

- 1. (Canceled).
- 2. (Currently amended) The method of claim 1, A method for gamut mapping of an input image using a space varying algorithm, comprising:

receiving the input image;

converting the color representations of an image pixel set to produce a corresponding electrical values set:

applying the space varying algorithm to the electrical values set to produce a color-mapped value set:

reconverting the color-mapped value set to an output image; and

wherein the space varying algorithm minimizes a the following variational problem represented by:

 $E(u) = \int_{\Omega} (D^2 + \alpha |\nabla D|^2) d\Omega$ , subject to  $u \in \mathcal{G}$ , wherein  $\Omega$  is a support of the input

image,  $\underline{\vartheta}$  is the target gamut,  $\alpha$  is a non-negative real number,  $D=g^*(u-u_0)$ , g is a normalized Gaussian kernel with zero mean and a small variance  $\sigma$ ,  $u_0$  is the input image, and u is the output image.

Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

3. (Original) The method of claim 2, further comprising: solving the variational problem at a high value of  $\alpha$ ; solving the variational problem at a low value of  $\alpha$ ; and averaging the solutions.

4. (Original) The method of claim 3, wherein the step of averaging the solutions comprises using a spatially adaptive weighting scheme, comprising:

$$u_{final}[k,j] = w[k,j]u_{small}[k,j](1-w[k,j])u_{high}[k,j],$$

wherein the weight w[k,j], comprises:

$$w[k,j] = \frac{1}{1 + \beta |\nabla g * u_0|^2}$$
, and

wherein  $\beta$  is a non-negative real number.

5. (Original) The method of claim 2, wherein the variational problem is solved according to:

$$\frac{du}{dt} = \alpha g * \Delta D - g * D, \text{ subject to } u \in \mathcal{G}.$$

6. (Original) The method claim 2, wherein the space varying algorithm is solved according to:

$$u_{ij}^{n+1} = u_{ij}^n + \tau(\alpha L_{ij}^n - \overline{D_{ij}^n})$$
, subject to  $u_{ij}^n \in \mathcal{S}$ , wherein

$$\tau = dt$$
,

$$D^n = g * g * (u^n - u_0)$$

Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

$$L^{n} = D_{2} * (u^{n} - u_{0})$$
 and

$$D_2 = g_x * g_x + g_y * g_y$$

7. (Currently amended) The method of claim 1, A method for gamut mapping of an input image using a space varying algorithm, comprising:

receiving the input image;

converting the color representations of an image pixel set to produce a corresponding electrical values set;

applying the space varying algorithm to the electrical values set to produce a colormapped value set;

reconverting the color-mapped value set to an output image; and

wherein the space varying algorithm minimizes a the following variational problem represented by:

$$E(u) = \int_{\Omega} (\rho(D) + \alpha \rho_2(|\nabla D|)) d\Omega$$
, subject to  $u \in \mathcal{S}$ , wherein  $\rho_1$  and  $\rho_2$  are scalar

functions,  $\Omega$  is a support of the image,  $\vartheta$  is the target gamut,  $\alpha$  is a non-negative real number,  $D=g^*(u-u_0)$ , g is a normalized Gaussian kernel with zero mean and a small variance  $\sigma$ ,  $u_0$  is the input image, and u is the output image.

8. (Original) The method of claim 2, further comprising:

decimating the input image to create one or more resolution layers, wherein the one or more resolution layers comprises an image pyramid; and

solving the variational problem for each of the one or more resolution layers.

PATENT Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

9. (Currently amended) The method of claim [[1]]2, wherein the method is executed in at least one of a camera and a printer.

- 10. (Currently amended) The method of claim [[1]]7, wherein the method is executed in at least one of a camera and a printer.
  - 11. (Canceled).
  - 12. (Canceled).
- 13. (Original) The computer readable memory of claim-12, A computer-readable memory for color gamut mapping, comprising an instruction set for executing color gamut mapping steps, the steps, comprising:

values, wherein output values are constrained within a gamut of the output device; using a space varying algorithm that solves an image difference problem; and

optimizing a solution to the image difference problem, wherein the image difference problem is represented by:

$$E(u) = \int_{\Omega} (D^2 + \alpha |\nabla D|^2) d\Omega$$

subject to  $u \in \mathcal{G}$ , wherein  $\Omega$  is a support of an input image,  $\alpha$  is a non-negative real number,  $\underline{9}$  is the target gamut,  $D=g^*(u-u_0)$ , g is a normalized Gaussian kernel with zero mean and small variance  $\sigma$ ,  $u_0$  is the input image, and u is an output image.

Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

14. (Currently amended) The computer-readable memory of claim [[12]]13, wherein the instruction set further comprises steps for:

solving the image difference problem at a high value of  $\alpha$ ; solving the image difference problem at a low value of  $\alpha$ ; and averaging the solutions.

15. (Original) The computer-readable memory of claim 14, wherein averaging the solutions comprises using a spatially adaptive weighting scheme, comprising:

$$u_{final}[k,j] = w[k,j]u_{small}[k,j](1-w[k,j])u_{high}[k,j],$$

wherein the weight w[k,j], comprises:

$$w[k,j] = \frac{1}{1 + \beta |\nabla g * u_0|^2}$$
, and

wherein  $\beta$  is a non-negative real number.

16. (Currently amended) The computer-readable memory of claim 12, A computer-readable memory for color gamut mapping, comprising an instruction set for executing color gamut mapping steps, the steps, comprising:

values, wherein output values are constrained within a gamut of the output device; using a space varying algorithm that solves an image difference problem; and

optimizing a solution to the image difference problem, wherein the image difference problem is represented by:

$$E(u) = \int_{\Omega} (\rho(D) + \alpha \rho_2(|\nabla D|)) d\Omega$$
, wherein  $\rho_1$  and  $\rho_2$  are scalar functions.

Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

17. (Currently amended) The computer readable memory of claim 12, A computer-readable memory for color gamut mapping, comprising an instruction set for executing color gamut mapping steps, the steps, comprising:

converting first colorimetric values of an original image to second colorimetric

values, wherein output values are constrained within a gamut of the output device; using a

space varying algorithm that solves an image difference problem; and

optimizing a solution to the image difference problem, wherein the instruction set further comprises steps for:

decimating the input image to create one or more resolution layers, wherein the one or more resolution layers comprise an image pyramid; and

solving the image difference problem for each of the one or more resolution layers.

- 18. (Original) The computer-readable memory of claim 17, wherein the instruction set further comprises steps for:
  - (a) initializing a first resolution layer;
  - (b) calculating a gradient G for the resolution layer, the gradient G comprising:

 $G = \Delta(u - u_0) + \alpha_K(u - u_0)$ , wherein  $\Delta x$  is a convolution of each color plane of x with

$$K_{LAP} = \begin{bmatrix} 0 & 1 & 0 \\ 1 & -2 & 1 \\ 0 & 1 & 0 \end{bmatrix}$$
 and  $\alpha_k = \alpha_0 * 2^{2(k-1)}$ ;

(c) calculating a normalized steepest descent value  $L_j = L_{j-1} - \mu_0 * \mu_{NSD} * G$ , wherein  $\mu_0$  is a constant;

PATENT Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

(d) projecting the value onto constraints  $\operatorname{Proj}_{\theta}(L_j)$ , wherein  $\operatorname{Proj}_{\theta}(x)$  is a projection of x into a gamut  $\theta$ ; and

- (e) for a subsequent resolution layer, repeating steps (b) (d).
- 19. (Original) A method for image enhancement using gamut mapping, comprising: receiving a input image;

from the input image, constructing an image pyramid having a plurality of resolution layers;

processing each resolution layer, wherein the processing includes completing a gradient iteration, by:

calculating a gradient G;

completing a gradient descent iteration; and

projecting the completed gradient descent iteration onto constraints; and computing an output image using the processed resolution layers.

20. (Original) The method of claim 19, wherein the gradient G, comprises:

$$G = \Delta(u-u_0) \ \alpha_k(u-u_0),$$

wherein u is the output image,  $u_0$  is the input image, and  $\alpha$  is a non-negative real number.

Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

21. (Original) The method of claim 19, wherein completing the gradient descent iteration comprises calculating:

$$\mu_{NSD} = \sum_{k} G^{2} (\Sigma(G * \Delta G) + \alpha_{k} \Sigma G^{2})$$
; and

$$L_j = L_{j-1} - \mu_0 \cdot \mu_{NSD} \cdot G,$$

wherein  $\mu_{NSD}$  is a normalized steepest descent parameter,  $\mu_0$  is a constant, k is a number of resolution layers in the image pyramid, and j is a specific resolution layer.

22. (Original) The method of claim 19, wherein projecting the completed gradient descent iteration onto the constraints is given by:

$$L_i = Proj_a(L_i),$$

wherein  $Proj_a(x)$  is a projection of x into a gamut  $\vartheta$ .

23. (Original) The method of claim 19, wherein constructing the image pyramid, comprises:

smoothing the input image with a Gaussian kernel;

decimating the input image; and

setting initial conductive  $L_0 = \max \{Sp\}$ , wherein Sp is an image with the coarsest resolution layer for the image pyramid.

Atty Docket No.: 10005732-1 App. Ser. No.: 09/882, 038

24. (Original) The method of claim 23, wherein the Gaussian kernel, comprises:

$$K_{PYR} = \begin{bmatrix} \frac{1}{16} & \frac{1}{8} & \frac{1}{16} \\ \frac{1}{8} & \frac{1}{4} & \frac{1}{8} \\ \frac{1}{16} & \frac{1}{8} & \frac{1}{16} \end{bmatrix}$$

25. (Currently amended) The method of claim 19, wherein processing each resolution layer further comprises applying a space varying algorithm to minimize a-the following variational problem represented by:

$$E(u) = \int_{\Omega} (D^2 + \alpha |\nabla D|^2) d\Omega$$
, subject to  $u \in \mathcal{G}$ , wherein  $\Omega$  is a support of the

image,  $\underline{9}$  is the target gamut, and D=g\*(u- $u_0$ ), wherein g is a normalized Gaussian kernel with zero mean and small variance  $\sigma$ ,  $u_0$  is the input image, u is the output image, and wherein  $\alpha$  is a non-negative real number.

26. (Original) The method of claim 19, wherein processing each resolution layer comprises applying a space varying algorithm to minimize a variational problem represented by:

$$E(u) = \int_{\Omega} (\rho(D) + \alpha \rho_2(|\nabla D|)) d\Omega$$
, subject to  $u \in \mathcal{S}$ , wherein  $\rho_1$  and  $\rho_2$ 

are scalar function.

27. (Original) The method of claim 26, wherein  $\rho 1$  and  $\rho 2$  are chosen from the group comprising  $\rho(x) = |x|$  and  $\rho(x) = \sqrt{1 + x^2}$ .